

In the claims:

B3 11 1. (currently amended) Wiper blade for window panes in motor vehicles, with comprising an elongated rubber-elastic wiping strip (20) which can contact the window pane (14) and is provided at both of its longitudinal sides (30) with open-edged longitudinal receiving grooves (32) which are arranged in a plane approximately parallel to the window pane and in which ~~a strip-like,~~ at least two strip-shaped elongated, resilient separate carrying rails (12) ~~is~~ are accommodated, ~~in each instance, the~~ inner edges of the carrying rails (12) which face one another contact a longitudinal web (36) of the wiping strip remaining between the grooves (32) and the two carrying rails (12) are secured in their receiving grooves transverse to their longitudinal extension by a holder (16) which is <sup>are piece</sup> provided with means for connection of a wiper arm and arranged at the ~~an~~ upper strip surfaces (13) of the carrying rails remote of the window pane, wherein the holder is provided with L-shaped claws (46), ~~the~~ each having two legs with a first L-leg (48) traversing the outer edges (52) of the carrying rails and the second L-leg (50) engaging under the respective carrying rail (12), ~~characterized in that~~ the and a distance (60) measured transverse to the longitudinal extension of the wiper blade (10) between the inner edges of the first L-leg (48) which face one another at least in a region of the L-legs is less than the sum of the

width (62) of the two carrying rails (12) plus the width (46) of the longitudinal web (36) of the wiping strip (20), and the wiper strip (20) provided with the carrying rails (12) is held by tension produced in the longitudinal web (36).

2. ~~(currently amended)~~ Wiper blade according to claim 1, ~~characterized in that~~ wherein each of the two carrying rails (12) projects out of its receiving groove (32) at least along a longitudinal portion by an edge strip, and in that the second L-legs (50) engage the lower strip surface (19) of their carrying rails (12) which faces the window pane (14).

B3 3. (currently amended) Wiper blade according to claims 1, ~~characterized in that~~ wherein the holder (16) has a ~~plate-like~~ plate-shaped body (42) which is supported at the upper strip surfaces (13) of the carrying rails (12), the first L-legs (48) of the claws (46) being connected with longitudinal sides (44) of this ~~plate-like~~ plate-shaped body (42) that are located opposite one another.

4. (currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein the claws (46) are arranged at the longitudinal sides (44) by pairs located opposite one another.

5. (Currently amended) Wiper blade according to claim 3, ~~characterized in that~~ wherein the body (42) of the holder (16) is provided at its underside facing the upper strip surfaces (13) of the two carrying rails (12) with a longitudinal cutout (54) for receiving a cover strip (40) of the wiping strip (20) defining the width of the two receiving grooves (32).

6. (Currently amended) Wiper blade according to claim 1 to 5, ~~characterized in that~~ wherein the holder (16) is provided with means (48) for connecting the wiper arm (18).

B3 7. (Currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein the lower strip surfaces (19) of the two carrying rails (12) together enclose an angle ( $\alpha$ ) that is less than 180°.

8. (Currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein the holder (16) is made of plastic.

9. (Currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein the holder (16) is made of metal.

10. (Currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein each carrying rail (112, 212, 312, respectively) is provided with at least one projection (116, 216, 316, respectively) at its inner longitudinal edges (114, 214, 314, respectively) facing the longitudinal ~~web (36) of the wiping strip (20).~~

11. (Currently amended) Wiper blade according to claim 1, ~~characterized in that~~ wherein the projection (116) of one carrying rail (112) is located opposite to the projection (116) of the other carrying rail (112).

B3 12. (Currently amended) Wiper blade according to claim 10, ~~characterized in that~~ wherein the projection (216) of one carrying rail (212) is arranged so as to be offset with respect to the projection (216) of the other carrying rail (212) in its longitudinal direction.

13. (Currently amended) Wiper blade according to claim 10, ~~characterized in that~~ wherein a recess (318) of one carrying rail (312 or 313) is located opposite to the projection (316) of the other carrying rail (312 or 313).

14. (Previously presented) Method for mounting a wiper blade constructed in accordance with claim 1, characterized in that the carrying rails (12) are introduced into their receiving grooves (32) and their upper strip surfaces (13) are tilted relative to one another in such a way that, together, ~~they enclose an angle ( $\beta$ ) of less than 180°~~, in that the carrying rails (12) are then <sup>laterally</sup> inserted together with the wiping strip (20) into the existing space (80) between the claws (46) arranged at the oppositely located longitudinal sides (44) of the holder (16), in which space (80) the carrying rails (12), when released, automatically attain their operating position and are fixed in the holder (16) together with the wiping strip (20) by the resulting tension of the longitudinal web (36).